













IMPACT RESISTANCE VERIFIED





Automatic bollards with integrated hydraulic unit

Perfect for managing urban and commercial access

The automatic bollards of the **P Series** are the ideal choice for managing urban traffic and controlling access in historic centers, residential areas, corporate parking lots, and commercial zones. Thanks to the integrated hydraulic technology, they ensure continuous and safe operation even under heavy traffic conditions.

- Smart access control for historic centers and Limited Traffic Zones (ZTL)
- Protection for private and commercial parking areas with high flow
- Resistance up to 250,000 J to meet urban requirements
- Reliable performance in intensive cycles, up to 2000 cycles/day
- Simultaneous management of multiple bollards
- Various configurations for **perfect integration** in urban settings.



Easier maintenance when choosing the removable hydraulic unit



Standard configuration

The standard configuration of our systems is designed to ensure efficiency, safety and ease of management. The configuration includes:

- Anthracite grey painted steel bollard, a device for controlling vehicle access
- Steel foundation box with aluminium zinc coating, an underground structure housing the bollard
- Control unit, manages the operation of the bollard.



Pilomat S.r.l. Via Zanica 17/P, Grassobbio (BG) Italia pilomat@pilomat.com www.pilomat.com














275/P-600A / 275/P-800A

Automatic bollards with integrated hydraulic unit

	275/P-600A	275/P-800A
Cylinder material	S235JR normal steel - X5CrNi 18-10 (AISI 304) - X5CrNiMo 17-12-2 (AISI 316) stainless steel	
Cylinder diameter	273 _{mm}	
Cylinder height	600mm	800mm
Cylinder thickness	6mm (optional AISI 316: 4mm)	
Movement principle	Hydraulic	
Cylinder normal steel finish	Anti-corrosion treatment - grey anthracite standard painting	
Cylinder stainless steel finish	Grey anthracite standard painting or brushing	
Reflecting adhesive strip	Standard - height 55mm	
Rising time	3,5s	4,5s
Lowering time	2s	2,5s
Emergency lowering	Standard (optional: automatic lowering)	
Safety reversal	Standard	
Connection line to control unit	Standard 10m (max 80m - with heating element max 50m)	
Voltage for control unit	230/400 VAC (+/- 10%) 50/60Hz	
Hydraulic pump	Built-in the bollard	
Protection class	IP 67	
Type of use	2000 Cycles/day	
Life units	3.000.000 Cycles	
Impact resistance	40.000 J (approved by TÜV Rheinland)	
Breakout resistance	250.000 J	
Nominal operating temperature	-40°C +70°C (for low temperatures see heating resistance)	
Load class (EN124)	D400	




Impact resistance


40,000 J

Breakout resistance
250,000 J



Pilomat S.r.I. Via Zanica 17/P, Grassobbio (BG) Italia pilomat@pilomat.com www.pilomat.com

















Pilomat offers safety accessories for every installed system: including photocells, flashing lights acoustic and sensors for emergency vehicles. Each device is designed to ensure maximum efficiency, clear signaling and secure control.


275/P-600A / 275/P-800A

Automatic bollards with integrated hydraulic unit

Available finishes



Safety and visibility



LED lighting strip

function

Traffic light

Special design



-unctions





Pilomat S.r.l. Via Zanica 17/P, Grassobbio (BG) Italia pilomat@pilomat.com www.pilomat.com













275/P-600A / 275/P-800A

Automatic bollards with integrated hydraulic unit

Pilomat provide a complete range of **control devices**, designed to make the use of installed systems practical and immediate. Buttons, selector and remote controls allow users to operate the devices with a single gesture, **ensuring immediate**, **reliable control and intuitive management**.

Control devices











Key switch

Card reader

Numeric key pad

Finger scan

Hand transmitter

reader







Timer (week - year)



GSM activator



P-Connect



Cloud Unit W5-B





Pilomat S.r.I. Via Zanica 17/P, Grassobbio (BG) Italia pilomat@pilomat.com www.pilomat.com